



Machine Specification Data															
M/C No:	Manufacturer / Model	Clamp End									Injection End				Location Ring Size
		Clamp Force Tons	Min Shut Height	Max Shut Height	Max Day Light	Between Tie Bars H x V	Max Opening Stroke	Ejector Stroke	Number of Cores	Number of Sequential Valves	Max Shot Weight PS	Screw Diameter	Max Injection Pressure	Number Of Hot Runner Zones	
1	KM 1600 08100 / MX / 04	1600	700mm	1600mm	3400mm	1870 x 1420 mm	2700mm	350mm	6	8	4137g	105mm	1780 bar	32	250mm
2	Engel Duo 11050 / 1700	1700	800mm	1600mm	3350mm	1805 x 1405 mm	2250mm	300mm	6	8	5930g	120mm	2020 bar	32	250mm
3	KM 1100 / 8100 / MX	1100	600mm	1200mm	2600mm	1550 x 1250 mm	2000mm	300mm	6	8	4137g	105mm	1780 bar	32	250mm
4	KM GX 900 / 6100	900	500mm	1100mm	2100mm	1180 x 1000 mm	1600mm	300mm	8	12	2391g	95mm	1795 bar	48	250mm
5	KM GX 650 / 4300	650	450mm	800mm	1750mm	1100 x 960 mm	1150mm	250mm	8	12	1853g	90mm	1778 bar	48	250mm
6	KM 300 / 1900	300	330mm	N/A	1150mm	630 x 630 mm	820mm	200mm	3	1	953g	70mm	1777 bar	0	160mm
7	KM CX 160 / 750	160	300mm	N/A	950mm	520 x 520 mm	650mm	150mm	0	0	375g	50mm	1892 bar	8	160mm
9	KM GX-650 - 4300	650	450mm	800mm	1750mm	1100x 960mm	1340mm	171mm	8	12	1853g	90mm	1899bar	48	200mm
8	KM GX400/ 300	400	400mm	900mm	1650mm	920x830mm	1250mm	250mm	6	12	1464g	80mm	1855 bar	48	200mm